

ULTRASONIC BATH

USW SERIES

Precision cleaning for wide usage areas.

The new USW Series Ultrasonic Baths are ideal to support all application including laboratories in analytical, industrial, environmental and medical sectors.



TECHNICAL DATA

	HB 351	HB 371	HB 391	HB 3111
Tank Volume Max**	5.7 L	7.8 L	9 L	13 L
Tank Interior Size (WxL)	325x176 mm	325x176 mm	329x350 mm	329x350 mm
Tank Interior Height	150 mm	200 mm	100 mm	150 mm
Frequency	40 kHz	40 kHz	40 kHz	40 kHz
User Interface	-	Digital	Digital	Digital
Control	Turning Knob	Turning Knob	Turning Knob	Turning Knob
Water Draining	Quick Coupling	Quick Coupling	Quick Coupling	Quick Coupling
Water Filling	On Top	On Top	On Top	On Top
Timer	-	Yes	Yes	Yes
Accesories	Standard*	Standard*	Standard*	Standard*
Material in Contact	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Permissible Ambient Temperature	5-40°C	5-40°C	5-40°C	5-40°C
Permissible Relative Humidity	80%	80%	80%	80%
Voltage	220-240 V	220-240 V	220-240 V	220-240 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz

FUNCTIONAL AND INTUITIVE

- Ultrasonic baths are generally usedi in scientific, medical, electronic, laboratory and industrial applications where precision in cleaning is important.
- Intuitive and easy setting and operation.
- The USW Series offers different size options for cleaning and sample preparation applications.

ACCESORIES

- *Standard accesories include lid and standard basket. For additional accesories please contact for options.
- **USW Series Water Baths can be designed according to your special needs (volume, dimensions, frequency and accesories can be designed for your requirements).

Contact us to learn more about custom designed water baths.



FOR ALL YOUR QUESTIONS AND INQURIES

- ☑ info@debyetechnic.com
- (+90312) 485 40 42
- (+90312) 485 40 42
- \bigoplus www.debyetechnic.com
- in DEBYE TECHNIC

